

# NOZZLE OPTIONS FOR THE EF1 RC MONITOR



## SMOOTH BORE

Smooth Bore Tips—  
5/8" for 80 gpm (300 l/min)  
or 1" for 200 gpm (750 l/min)  
Good for CAFS Applications

Y1-E32A Monitor with FF152



## SELECTABLE

100 psi Selectable ER Tip  
Flow Capacity that ranges  
from 15 to 120 gpm  
(50 to 450 l/min)

Y1-E32A Monitor with B-TOS-ERP



## ULTIMATIC

75, 100, 120 or 150 psi  
Automatic Tip  
Flow Capacities that range  
from 10 to 125 gpm  
(35 to 470 l/min)

Y1-E32A Monitor with B-TO-ERP



## BUBBLE CUP

100 psi Dual Gallonage Tip  
Flow Capacities at  
20/60 gpm (75/230 l/min)  
or 20/95 gpm (75/360 l/min)  
Integrated Aspirated Foam Sleeve  
Integrated Nozzle Shut Off

Y1-E32A Monitor with FS2095BCER

## RC CONTROLLER OPTIONS

### BLUETOOTH®



YE-RF-BT  
Tactile Touch  
Controller



YE-BT1  
Bluetooth®  
Adapter

### PUMP PANEL



Panel Mount  
Monitor Operator  
Station

### HANDHELD W/30 FT TETHER

Tethered Monitor  
Operator Station



### JOYSTICK IN THE CAB



Joystick Monitor Operator Station  
with Valve Control. Available in a  
Gateable or Non-Gateable Version



Heavy Duty  
Stainless Steel Water  
Valve and Interface Box:  
Gateable Version or Non-Gateable  
Version

OEM INSTALLED PRODUCTS