

THREE BIG WATER NOZZLE OPTIONS!



MASTER STREAM 4000 ER

- Available in Automatic or Selectable
- Automatic: Adjustable Pressure with flow range of 600 to 4000 GPM (2400 to 16000 l/min)
- Selectable: 2000 and 4000 GPM (8000 and 16000 l/min) at 100 psi (7 bar)
- Available with either the Tsunami quick connect or 6" (152mm) ANSI 150 inlet
- Electric Remote nozzle that easily adjusts from straight stream to a dense fog pattern

The TSUNAMI is TFT's largest

highest volume industrial monitor for fixed, trailer, or apparatus use.

The monitor offers 2700 to 8000 gpm (10,000 to 30,000 l/min) flows in manual and RC versions.



VORTEX VERSATILITY

- Add to stacked tips for the ability to go from Straight Stream to Dispersed pattern with no loss to stream flow !
- Available in Electric Remote or Manual

STACKED TIPS



SMOOTH BORE SIZE: 3.5" (90mm)
FLOW RATE: 3260 gpm (12,340 l/min)
NOZZLE PRESSURE: 80psi (6 bar)
Industry Standard for Master Stream Stacked Tips



SMOOTH BORE SIZE: 4.5" (115mm)
FLOW RATE: 5380 gpm (20,360 l/min)
NOZZLE PRESSURE: 80psi (6 bar)
Industry Standard for Master Stream Stacked Tips



SMOOTH BORE SIZE: 4" (100mm)
FLOW RATE: 4250 gpm (16,090 l/min)
NOZZLE PRESSURE: 80psi (6 bar)
Industry Standard for Master Stream Stacked Tips



SMOOTH BORE SIZE: 5.125" (130mm)
FLOW RATE: 6980 gpm (26,420 l/min)
NOZZLE PRESSURE: 80psi (6 bar)
Industry Standard for Master Stream Stacked Tips