

# ADAPTERS

## WRENCHES AND TOOLS

### ADAPTER AA THREADED



AA threaded Adapters are permanently marked with the thread size and threads per inch per NFPA. 2.5" and smaller swivel connections use stainless steel ball bearings to ensure longevity and easy serviceability. 3.0" and larger connections use polymer bearing rings which provide electrical isolation to help prevent galvanic corrosion.

### ADAPTER AA STORZ



AA Storz adapters are permanently marked with the thread size and threads per inch per NFPA and include a red anodized aluminum locking lever. Connections use polymer bearing rings which provide electrical isolation to help prevent galvanic corrosion. All Storz adapters are supplied with pressure gaskets.

### ELBOWS THREADED



AH series of threaded elbows are cast to a 30-degree down angle for easy connection. Couplings are permanently marked with the thread size and threads per inch per NFPA. Hose couplings are attached using polymer bearing rings which provide electrical isolation to help prevent galvanic corrosion.

### ELBOWS STORZ



AH series of Storz elbows are cast to a 30-degree down angle for easy connection and to relieve the weight of the hose when connected. All Storz adapters are supplied with pressure gaskets. Suction gaskets are available. All 4" and 5" Storz couplings can be easily switched from rigid to swivel with a hex key.

←

AA series threaded and storz adapters are designed for pressure or vacuum service on a hydrant, pumper or on the ground. Maximum operating pressure is 300 psi (20 bar) and they are compliant to NFPA 1964 2018 edition. The aluminum parts are hardcoat anodized per MIL-A-8625F Type III, Class 2 for maximum corrosion protection.

→

←

TFT AH series threaded and Storz elbows maximum operating pressure is 300 psi (20 bar) and they are compliant to NFPA 1964 2018 edition which dictates a 900 psi (62 bar) hydrostatic strength test. The aluminum parts are hardcoat anodized per MIL-A-8625 Type III, Class 2 for maximum corrosion protection then powder coated silver.

→

### 90 DEGREE ELBOW



The AF series 90 Degree Elbow has a full-time ball bearing swivel that allows 360° rotation while coupling remains secured. The elbow has 1/4" NPT and 3/4" NPT ports to allow installation of a pressure gauge and/or bleeder.



The aluminum parts are hardcoat anodized per MIL-A-8625 Type III, Class 2 for maximum corrosion protection then powder coated silver. Hose couplings are attached using polymer bearing rings which provide electrical isolation to help prevent galvanic corrosion. Maximum operating pressure is 300 psi (20 bar).



### DETENT ELBOWS



TFT AJ series detent elbows are cast to a 30-degree down angle for easy connection and to relieve the weight of the hose when connected. The swivel includes multiple detent options that allow the elbow to swivel 360 degrees.

### BLIND CAPS ASSORTMENT



### HYDRANT ADAPTERS



### HOSE THREAD ADAPTERS



### TOOLS ASSORTMENT



**Download the Complete  
ADAPTERS, CAPS & PLUGS, COUPLINGS,  
ELBOWS, WRENCHES and TOOLS  
Catalog at [TFT.com](http://TFT.com)**



**MADE IN USA**

**800 · 348 · 2686**